

Data sheet

Rauch PRC 230N

inkjet paper mat with nano caoting

Product description:

Heavy mat coated paper with mat nano coating for high quality presentation plots with high color application. Special color receipt coat for brilliant color reproduction, smear-resistant drying. Very well siuted for Dye- and UV-pigmented ink.

Specific feature:

This product is particularly suitable for applications on color inkjet plotters with high ink application. PRC 230N is an inkjet paper, which convinces by full-surface-reproduction with good resolution, high marginal definition as well as very high brilliance of colors. By its high ink absorption a very fast drying process and a good water resistance is possible. PRC 230N always shows a clear, colorful output of text, photo and diagram. Very fast drying and smear resistance also of the intensively pigmented black ink. Therefore this special paper is recommended for the output of high quality presentation plots with high resolution and it is universal suitable for dye-, pigment, and latex inks.

The paper is also available in the same paper color in weights such as 140g, 120g, 100g, 90g und 230g

Processing:

For optimal printing results PRC 230N can be calibrated beforehand on the used printers and with the appropriate ink. Without calibration color modifications can occur. For quality reasons the processing and storage of the paper should take place in a climate of about 50% relative humidity and at a temperature of about 23°C. Keep in the original packaging cardboard box and PE bag.

Technical specification:

Material: **PAPIER**

Application Area: NUR IM INNENBEREICH

MATT Surface: 230,00g/m² Specific gravity: Thickness: 290,00µm nein R1-cert · Cold lamination: ja

Heat lamination: Opacity: 98% ±2 (DIN 53146) 97 ±1 (DIN 5033) Color L: Color a: 4 ±1 (DIN 5033) Color b: -14 ±1 (DIN 5033) UV-whiteness: 154% ±22 (ISO 11475) Smoothness (Bekk): 19s ±10 (ISO 5627)

ia

ph-value:

89mN ±22 (ISO 2493) Steifigkeit md: 46mN ±13 (ISO 2493) Steifigkeit cd:

DIN ISO 16245

IMO-COC-150296, FSC Mix Credit **FSC®**

This information consists of standard values for your guidance. Before using our print media, please check their suitability to your printer and for your intended application. Taking account of technical development, product specifications may be amended withou prior notice at any time. There is no guarantee that the same results can be achieved. We not accept liability for any errors resulting from technical changes in printers and / or inks