

# Data sheet

## DSR 170

Inkjet paper, both sides coated

### Product description:

Color paper mat, brilliant whiteness with a short drying time, both sides coated for high resolution, good handling.

### Specific feature:

The mat coated neutral-white surface of DSR 170 is homogenously closed and has a specially applied color receiving coat on both sides. Thus this special paper is recommended for high-quality double-sided presentation plots with high resolution. The product is suitable for the use on most of the common color inkjet plotters with dye-based and pigmented inks. DSR 170 is an inkjet paper, which convinces by intensive colors, definite precise reproduction of color surfaces, line-management and outline at short drying time. DSR 170 can be laminated cold and hot.

### Technical specification:

Material:	PAPIER
Application Area:	NUR IM INNENBEREICH
Surface:	MATT
Specific gravity:	170,00g/m <sup>2</sup>
Thickness:	218,00µm
B1-cert.:	nein
Cold lamination:	ja
Heat lamination:	ja
Color L:	96,1
Color a:	1,8
Color b:	-8,6
Whiteness (R457):	150
DIN ISO9706 archivable:	Ja
DIN ISO 16245	Nein

### Processing:

For optimum printing results, DSR 170 must be calibrated beforehand on the used printers and with the appropriate ink. For quality reasons the processing and storage of DSR 170 should take place in a climate from 35 to 65% relative humidity and at a temperature from 10-30°C. Storage: in original packing (carton box and PE-bag) at a cool and dry place, clean and dustfree.

This information consists of standard values for your guidance. Before using our print media, please check their suitability to your printer and for your intended application. Taking account of technical development, product specifications may be amended without prior notice at any time. There is no guarantee that the same results can be achieved. We not accept liability for any errors resulting from technical changes in printers and / or inks